

## H07RN-F TITANEX®

Industrial flexible cable, insulation and outer sheath in elastomer.  
 Oil resistant, flame retardant according to IEC/EN 60332-1-2 standard.

### Description

#### Application

H07RN-F TITANEX® flexible cable is intended for installations with moving equipment, electric appliances and for building sites. The cable may be rated 0,6/1 kV where the installation has built-in protection and for motors in lifting appliances - machine tools - etc.

This cable can be used in refrigerating installations.

#### Installation

This cable can be installed in open air or be buried but with extra mechanical protection.

#### Conductors laid up

Assembled conductors.

#### Nota

Max continuous operating conductor temperature in normal use :

+60°C ( in every case of mobile installation)

+85°C ( fixed protected installation )

+200°C ( in short circuit )

Permissible current rating is measured for an ambient temperature of 30°C and a maximum operating and conductor temperature of 85°C . For other temperature please refer to correction factors .



### Standards

**International** EN 50525-2-21;  
 HD 22.4; HD 516;  
 IEC 60245-4 type 66

**National** NF C 32-102-4

							
Lead free Yes	Mechanical resistance to impacts Very good	Cable flexibility Flexible	Chemical resistance Accidental	Water proof Intermittent	RoHS conform Yes	Operating temp. range -25 .. 55 °C	Oil resistance Yes

## H07RN-F TITANEX®

### Characteristics

Construction characteristics	
Conductor material	Bare copper
Insulation	Special cross-linked elastomer
Outer sheath	Special cross-linked elastomer
Sheath colour	Black
Lead free	Yes
Mechanical characteristics	
Mechanical resistance to impacts	Very good
Cable flexibility	Flexible
Usage characteristics	
Silicon free	Yes
Chemical resistance	Accidental
Water proof	Intermittent
RoHS conform	Yes
Operating temperature, range	-25 .. 55 °C
Short-circuit max. conductor temperature	200 °C
Oil resistance	Yes
Max. conductor temperature in service	85 °C

### Single Core

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Max. outer diam. [mm]	Min. outer diam. [mm]	Approx. weight [kg/km]
1.5	23	23.3	7.1	5.7	50
2.5	32	14.0	7.9	6.3	66
4	43	8.7	9.0	7.2	94
6	56	5.9	9.8	7.9	109
10	77	3.4	11.9	9.5	182
16	102	2.2	13.4	10.8	256
25	136	1.4	15.8	12.7	369
35	168	1.04	17.9	14.3	482
50	203	0.75	20.6	16.5	662
70	254	0.56	23.3	18.6	895
95	-	-	-	-	1144
120	363	0.36	28.6	22.8	1430
150	416	0.31	31.4	25.2	1740
185	475	0.28	34.4	27.6	2160
240	559	0.23	38.3	30.6	2730
500	833	0.16	52.0	41.3	5700

## H07RN-F TITANEX®

### Two cores

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Max. outer diam. [mm]	Min. outer diam. [mm]	Approx. weight [kg/km]
1	18	39.4	10.0	7.7	99
1.5	23	27.0	11.0	8.5	111
4	43	10.1	15.1	11.8	238
6	56	6.7	16.8	13.1	279
10	77	3.8	22.6	17.7	538
16	102	2.5	25.7	20.2	744
25	136	1.68	30.7	24.3	1074

### Three cores

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Max. outer diam. [mm]	Min. outer diam. [mm]	Approx. weight [kg/km]
1	18	39.4	10.7	8.3	117
1.5	23	27.0	11.9	9.2	134
1.5	23	27.0	11.9	9.2	134
2.5	32	16.2	14.0	10.9	195
2.5	32	16.2	14.0	10.9	195
4	43	10.1	16.2	12.7	290
6	56	7.0	18.0	14.1	346
10	77	4.0	24.2	19.1	663
16	102	2.5	27.6	21.8	924
25	136	1.7	33.0	26.1	1345
35	168	1.21	37.1	29.3	1760
50	203	0.87	42.9	34.1	2390
70	262	0.64	48.3	38.4	3110
95	320	0.5	54.0	43.3	4170
120	373	0.4	60.0	47.4	5080
150	432	0.35	66.0	52.0	6220
185	495	0.3	72.0	57.0	7730
240	587	0.26	82.0	65.0	9780
300	680	0.22	90.0	72.0	12620

### Four cores

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Max. outer diam. [mm]	Min. outer diam. [mm]	Approx. weight [kg/km]
1	16	34.08	12.0	9.6	144
1.5	21	23.3	13.1	10.2	165
1.5	21	23.3	13.1	10.2	165
2.5	29	14.0	15.5	12.5	245
4	38	8.71	18.0	14.0	357
6	50	5.84	20.0	15.7	443

## H07RN-F TITANEX®

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Max. outer diam. [mm]	Min. outer diam. [mm]	Approx. weight [kg/km]
10	68	3.42	26.5	20.8	818
16	92	2.2	30.1	23.8	1150
25	122	1.44	36.6	28.9	1700
35	150	1.04	41.1	32.5	2180
50	182	0.75	47.5	37.7	3030
70	232	0.56	54.0	42.7	3990
95	281	0.44	61.0	48.4	5360
120	325	0.36	66.0	53.0	6500
150	373	0.31	73.0	58.0	7990
185	425	0.28	80.0	64.0	9910
240	500	0.23	91.0	72.0	13120

### Five cores

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Max. outer diam. [mm]	Min. outer diam. [mm]	Approx. weight [kg/km]
1	16	34.1	14.0	10.9	180
1.5	21	23.6	14.4	11.2	238
2.5	29	14.0	17.0	13.3	297
4	38	8.72	19.9	15.6	453
6	50	5.84	22.2	17.5	557
10	68	3.43	29.1	22.9	1001
16	92	2.2	33.3	26.4	1430
25	122	1.44	40.4	32.0	2096

### Seven cores

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Max. outer diam. [mm]	Min. outer diam. [mm]	Approx. weight [kg/km]
1.5	-	-	-	-	349
2.5	-	-	21.8	17.1	487

### Twelve cores

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Max. outer diam. [mm]	Min. outer diam. [mm]	Approx. weight [kg/km]
1.5	11	23.3	22.14	17.6	510
2.5	-	-	-	-	702

### Eighteen cores

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Max. outer diam. [mm]	Min. outer diam. [mm]	Approx. weight [kg/km]
1.5	9	20.7	26.3	20.7	730

## H07RN-F TITANEX®

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Max. outer diam. [mm]	Min. outer diam. [mm]	Approx. weight [kg/km]
2.5	-	-	-	-	1018

### twenty four cores

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
1.5	8	-	24.3	30.7	1000

### thirty six cores

Cross section [mm <sup>2</sup> ]	Perm. current rating open air [A]	Voltage drop, single phase [V/A.km]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
1.5	6	-	27.8	35.2	1325
2.5	-	-	-	-	1879

### New cores identification

Core identification in accordance with HD 308 S2 - Identification of cores in cables and flexible cords.

Number of cores	HD 308 S2 since january 2004	
	G (earth core)	X (without earth core)
1		Black (preferential)
2		Blue + Brown
3*	Green - Yellow + Blue + Brown	Brown + Black + Grey
3**		Blue + Brown + Black
4	Green - Yellow + Brown + Black + Grey	Blue + Brown + Black + Grey
5	Green - Yellow + Blue + Brown + Black + Grey	Blue + Brown + Black + Grey + Black
> 5	White printed numbers + 1 Green - Yellow	White printed numbers

\* For the cables without Green/Yellow with a cross-section >4mm<sup>2</sup>

\*\* For the cables without Green/Yellow with a cross-section of 1,5mm<sup>2</sup> & 2,5mm<sup>2</sup>

### Selling information

#### Marking

USE <HAR> H07RN-F N (x ou G) S mm<sup>2</sup> TITANEX®

N = number of cores

- G = with Green-Yellow
- x = without Green-Yellow
- S = section in mm<sup>2</sup>